

Premier Model		R30	R45 or R45E	R60 or R60E	OHV30	OHV40	OHV50H	OHV60 or OHV60E	OHV110E	OHV85E	OHV100E
<b>GENERAL FEATURES</b>	Switchless Full Pow'R		•	•		•	•	•	•	•	•
	AC Voltmeter		•	•		•	•	•	•	•	•
	Hourmeter	•	•	•	•	•	•	•	•	•	•
	AC Circuit Breakers	•	•	•	•	•	•	•	•	•	•
	Low Oil Shutdown	•	•	•	•	•	•	•	•	•	•
	Automatic Idler	•	•	•		•	•	•		•	•
	Voltage Regulation								•		•
	Spark Arrestor Muffler	•	•	•	•	•	•	•	•	•	•
	Extended Run Fuel Tanks	•	•	•	•	•	•	•	•	•	•
	Tubular Roll Cage	•	•	•	•	•	•	•	•	•	•
	Neoprene Isolators	•	•	•	•	•	•	•	•	•	•
	Focal Vibration System (FVS)		•	•		•	•	•	•	•	•
	*3 Year Commercial Warranty	•	•	•	•	•	•	•	•	•	•
<b>SPECIFICATIONS</b>	<b>Engine</b>	<b>Robin/ Subaru</b>	<b>Robin/ Subaru</b>	<b>Robin/ Subaru</b>	<b>Honda</b>	<b>Honda</b>	<b>Honda</b>	<b>Honda</b>	<b>Honda</b>	<b>Vanguard</b>	<b>Vanguard</b>
	<b>Model</b>	<b>EH17</b>	<b>EH25</b>	<b>EH34</b>	<b>GX160</b>	<b>GX240</b>	<b>X270</b>	<b>GX340</b>	<b>GX620</b>	<b>303477</b>	<b>350477</b>
	Horsepower	5.5 Hp	8.0 Hp	11.0 Hp	5.5 Hp	8.0 Hp	9.0 Hp	11.0 Hp	20.0Hp	16.0 Hp	18.0 Hp
	Cylinder(s)	1	1	1	1	1	1	1	2	2	2
	Displacement – cc	172	231	338	163	242	270	337	614	480	570
	Lubrication System	Splash	Splash	Splash	Splash	Splash	Splash	Splash	Pressure	Pressure	Pressure
	Starting Systems (Battery not included on Electric Start models)	Recoil	Recoil or 12 Volt with Recoil	Recoil or 12 Volt with Recoil	Recoil	Recoil	Recoil	Recoil or 12 Volt with Recoil	12 Volt Electric	12 Volt with Recoil	12 Volt with Recoil
	<b>Rating</b>	3000W Max.	4500W Max.	6000W Max.	3000W Max.	4000W Max.	5000W Max.	6000W Max.	11,000W Max.	9000W Max.	10,500W Max.
		2500W Rated	4000W Rated	5000W Rated	2500W Rated	3500W Rated	4000W Rated	5000W Rated	10,000W Rated	8000W Rated	9,500W Rated
		120V AC	120/240V AC	120/240V AC	120V AC	120/240V AC	120/240V AC	120/240V AC	120/240V AC	120/240V AC	120/240V AC
		20.8A	33.3/16.7A	41.6/20.8A	20.8A	29.2/14.6	33.3/16.7A	41.6/20.8A	83.3/41.6A	66.7/33.4A	79.2/39.6A
	<b>Sound Ratings</b> db(A) at 23 feet (7 meters)	66.9	70.9	72.8	69.9	73.0	73.0	72.4	78.0	75.4	75.3
	<b>Receptacles</b>										
	Straight (5-20R GFCI) 120V	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp	4-20 Amp
	Twist Lock (L530R) 120V		1-30 Amp	1-30 Amp		1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp
	Twist Lock (L1430R) 120/240V		1-30 Amp	1-30 Amp		1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp	1-30 Amp
	Twist Lock (CS6369) 120/240V								1-50 Amp		1-50 Amp
	Fuel Capacity (U.S. gallons)	3.2	4.4	4.4	2.8	4.6	4.6	4.6	5.8	5.8	5.8
	Operational Run Time /1 tankful	6-9 hours	5-9 hours	4.5-8 hours	5-8 hours	6-10 hours	6-10 hours	4-7 hours	4-6 hours	4-7 hours	4-6 hours
	<b>Dimensions</b>										
	Length	22 1/2"	27"	27"	25 1/2"	28"	28"	28"	30"	28"	30"
Width	15 3/4"	18 1/4"	18 1/4"	17 1/2"	20 1/2"	20 1/2"	20 1/2"	23"	21 1/2"	23"	
Height	20 1/2"	23 1/4"	23 1/4"	18"	22 1/4"	22 1/4"	22 1/4"	28 1/2"	27 1/2"	28 1/2"	
		(20 1/4"W-R45E)	(20 1/4"W-R60E)								
<b>Weight</b>											
Net Dry	110 lbs.	170 lbs./175 lbs.	195 lbs./200 lbs.	112 lbs.	170 lbs.	170 lbs.	192 lbs./206 lbs.	270 lbs.	224 lbs.	270 lbs.	

**WARNING:** Do not connect generator to any building's electrical system unless a disconnect switch has been installed.

**NOTES:** • Due to our continuing effort for product improvement, specifications subject to change without notice.  
\* Engine warranty per manufacturer.

**BALDOR**  
**GENERATORS**

